
## SolidLock<sup>®</sup> STATIC SEAL

## HEAVY DUTY CENTRIFUGAL PUMPS

#### The ultimate static seal for the toughest slurry applications

The SolidLock<sup>®</sup> static seal, combined with the Wilfley dynamic expeller, is the perfect sealing solution for any pumping application that contains solids. The SolidLock<sup>®</sup> has proven to be a superior alternative to conventional sealing technologies.



#### PUMP OFF / SEAL CLOSED

#### PUMP RUNNING / SEAL OPEN

The SolidLock<sup>®</sup> has a simple but very effective design. Upon start up, centrifugal forces act upon governor weights to open the seal faces and preclude any seal drag and wear. At shut down, isolated springs force the seal faces to close prior to the transition of dynamic sealing to static. The ingenious, self-enclosing design of the proprietary stationary seal face will flex outwards against the rotary seal face to eliminate leakage due to increased internal pressure.

#### The SolidLock<sup>®</sup> couldn't be easier to install and maintain:

- Retrofit kits are available to convert existing Wilfley pumps in the field
- The cartridge style assembly is designed for straight-forward installation
- The seal actuating speed can be easily adjusted without disassembling the pump

### Currently Available On These Wilfley Pumps: EMW® SLURRY PUMP KPRO® SLURRY PUMP HD SLURRY PUMP S3 ACID SLURRY PUMP A9 CHEMICAL PUMP A7 CHEMICAL PUMP AF CHEMICAL PUMP


 5870 E. 56th Ave. • Commerce City, CO 80022 USA • Toll Free: 1-800-525-9930 • Phone: +1 (303) 779-1777 • Fax: +1 (303) 779-1277

 Page 1 of 2

 www.wilfley.com • pumps@wilfley.com

 Rev 2 - December 2015

# SolidLock<sup>®</sup> STATIC SEAL



| Part No.         | Description                           | Qty. |
|------------------|---------------------------------------|------|
| S1A              | Stationary Seal Housing               | 1    |
| S1D              | Stationary Seal                       | 1    |
| S1E              | Seal Lock                             | 1    |
| S1F              | Stationary Seal Bolts                 | 4-6  |
| S2A              | Rotary Seal                           | 1    |
| S2B              | Rotary Seal Bolts                     | 4    |
| S2C              | Rotary Seal Carrier                   | 1    |
| S2D              | Weight Spider                         | 1    |
| S2E              | Weights                               | 2    |
| S2F              | Spring Bolts                          | TBD1 |
| S2G              | Springs                               | TBD1 |
| S2H              | Pull Pin                              | 2    |
| S2J              | Weight Bolts                          | 2    |
| S2K              | O-Ring, Rotary Seal                   | 1    |
| S2L              | O-Ring, Rotary Seal Carrier           | 1    |
| S2M              | O-Ring, Weight Spider                 | 1    |
| S2N              | O-Ring, Weight Spider to Shaft Sleeve | 1    |
| S2P              | Shaft Sleeve Set Screws               | 4    |
| TBD <sup>2</sup> | Shaft Sleeve                          | 1    |

1. Quantity varies with pump size and operating speed.

2. Part number varies with pump model.

#### **Purge Port Configuration**

